

## ESKV-RDE 32

Cable gland with reduction sealing insert, polyamide, M32, RAL 7001



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



|                          |                           |
|--------------------------|---------------------------|
| Material cable gland     | Polyamide                 |
| Material sealing gasket  | EPDM                      |
| Temp. range min          | -40 °C                    |
| Temp. range max          | 100 °C                    |
| Protection class         | IP69, IP68 (5 bar 30 min) |
| Thread type              | M                         |
| Ø Connection thread D    | 32                        |
| Lead                     | 1,5                       |
| Length screw-in thread L | 12 mm                     |
| Ø cable diameter min     | 9 mm                      |
| Ø cable diameter max     | 21 mm                     |
| Key width SW             | 36 mm                     |
| Collar diameter (E)      | 40 mm                     |
| Total length TL          | 42 mm - 51 mm             |
| Glow wire test           | 750 °C                    |
| Type of cable anchorage  | A                         |
| Install. torques fitting | 15 N m                    |
| Install. torques cap nut | 4 N m                     |
| Impact category          | 4                         |
| Advice                   | With reduction insert     |
| Product Color            | RAL 7001                  |
| Order no. RAL 7001       | 10064988                  |
| Type                     | ESKV-RDE 32               |
| Packing unit             | 25                        |
| ETIM-Classification      | EC000441                  |

Recommended accessories

|                |          |
|----------------|----------|
| <b>EMUG 32</b> | 10062716 |
| <b>EADR 32</b> | 10062805 |
| <b>BS 14</b>   | 10064011 |

22.06.2018

